

EXTREME ENVIRONMENTS

FEATURED PRODUCTS

- Accelerometers
- Pressure transducers
- Signal conditioners
- Inertial sensors
- Cable assemblies
- Supporting instrumentation
- Calibration equipment



Featured products

Piezoelectric accelerometers



6222S High temp accelerometer

- Balanced differential output
- High sensitivity in a low profile package
- Robust ARINC 3-point mounting
- +500°F(+260°C) continuous operation



7703A Radiation hardened accelerometer

- Extremely stable Isoshear design
- Radiation environment up to 10^8 rads
- Hermetically sealed
- +550°F (+288°C) operation



2222C Micro miniature accelerometer

- Adhesive mounted accelerometer
- Light weight (0.5 grams) eliminates mass loading effects
- Excellent output stability over time

Isotron accelerometers



7250B/BM1 High frequency accelerometer

- Measures up to 40KHz
- 360° cable orientation
- Lightweight (1.8 grams)



65HTLPF Triaxial accelerometer

- Integral 2-pole low pass filter in front of charge amplifier
- 10 mV/g sensitivity
- 347°F (+175°C) operation
- Small size (10-mm cube, 5 grams)



2256B General purpose accelerometer

- Adhesive mount, top connector
- Signal ground isolated from mounting surface
- Small & lightweight (4 grams)
- Available with 10 mV/g or 100 mV/g sensitivity

Inertial sensors



7310A Angular rate sensor

- 7 ranges from 100 to 18,000 deg/sec
- ISO 17025 certified calibration
- Measures rotational velocity
- Accurate in shock environment
- 5 to 16 V excitation
- Weighs less than 3 grams



7360A 6 Degrees of freedom sensor

- Three axes of acceleration and three axes of rate sensor
- Compact package with two 12 conductor integral cables
- ISO17025 certified calibration
- Option M1 for 5V operation



7280AM7 High g accelerometer

- 2K, 20K and 60K g full scale ranges
- Extremely rugged
- Lightly damped
- Robust low noise cable
- Low power consumption

Piezoresistive accelerometers

Variable capacitance accelerometers



770A-770F DC accelerometers

- 2, 10, 30, 50, 100 and 200 g ranges
- Rugged Al housing
- 28 AWG cable
- Adhesive or screw mount



773 Triaxial low g DC accelerometer

- Triaxial accelerometer
- 2, 10, 30, 50, 100 and 200 g ranges
- Rugged Al housing
- Separate power & ground



771 Hermetic low g DC accelerometer

- 2, 10, 30, 50, 100 and 200 g ranges
- Hermetic SS package
- Military temperatures
- 0.625 inch hex base



35C Ultra-miniature triaxial accelerometer

- World's smallest triaxial IEPE
- Hermetic titanium housing
- Miniature, 0.235 inch cube
- Lightweight, 0.76 grams
- 2.5, 5 and 10 mV/g sensitivity options



7270AM7 High g accelerometer

- 2K, 6K, 20K, 60K and 200K g full scale ranges
- Extremely rugged
- Broad frequency response
- Undamped
- Robust low noise cable



728 Shock accelerometer

- 2,000 and 10,000 g full scale ranges
- Small, lightweight (0.5 grams)
- Broad bandwidth (0 to 8,000Hz +/-1dB)
- Damped
- Adhesive mount



713-713F Triaxial shock accelerometer

- Triaxial accelerometer
- 2000 g full scale range
- Multi-mode damping
- High sensitivity
- Adhesive or screw mount

Supportive instrumentation



4416C IEPE signal conditioner

- Portable compact size, battery powered
- Selectable gain: 1, 10, 100
- 2nd order Sallen Key 10 kHz low pass filter
- Single-channel



4830B Accelerometer simulator

- Battery operated, portable accelerometer simulator
- Simulates the electrical output signals generated by common measurement transducers
- Simplifies troubleshooting, verification, and calibration processes for test systems
- Ability to create, store, and recall up to 40 pre-set simulation profiles
- Adjustable, TTL based tachometer output
- Analyze vibration signals with built in FFT function



4418 Single channel bridge signal conditioner

- Designed for use with Endevco piezoresistive and variable capacitance accelerometers
- Portable compact size, battery operated
- Selectable gain: 1, 10, 100
- Easy ZMO adjust



2771CM2 Remote charge convertor

- Designed for use with extreme high temperature sensors (1200°F, 650°C)
- Wide frequency response
- Supports IEEE 1451.4 (TEDS)



10869 NC Highway 903, Halifax, NC 27839 USA

endevco.com | sales@endevco.com | 866 363 3826

© 2022 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevco is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevco), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.

EDV-FeaturedProducts-0422

Aufgrund laufender Weiterentwicklungen sind Änderungen der Spezifikationen vorbehalten. Alle Angaben vorbehaltlich Satz- und Druckfehler.

nbn Austria GmbH

Riesstraße 146, 8010 Graz

Tel. +43 316 40 28 05 | Fax +43 316 40 25 06

nbn@nbn.at | www.nbn.at

