

P/N: 29421-200

Copyright

© 2017, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 29421-200

Release:

Commit: 44554

Language: en-US

Modified: 2017-08-29

Formatted: 2017-09-14

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| | |
|----------------------------|--|
| Detector data | |
| Detector Type | Strained-Layer Superlattice |
| Spectral Range | 3 - 12 microns |
| Resolution | 640 x 512 |
| Detector Pitch | 25 µm |
| Thermal Sensitivity/NETD | < 40 mK |
| Well Capacity | 11.0 M electrons |
| Operability | > 99% (> 99.5% typical) |
| Sensor Cooling | Closed cycle rotary |
| Electronics | |
| Readout Type | Snapshot |
| Readout Modes | Asynchronous integrate while read Asynchronous integrate then read |
| Synchronization Modes | Genlock, Sync-in, Sync-out |
| Image Time Stamp | Internal IRIG-B decoder clock TSPI accurate time stamp |
| Integration Time | 270 ns to 687 sec |
| Pixel Clock | 355 MHz |
| Frame Rate (Full Window) | Programmable; 0.0015 Hz to 1004 Hz |
| Subwindow Mode | Flexible windowing down to 64 x 4 (steps of 32 columns, 4 rows) |
| Dynamic Range | 14-bit |
| On-Camera Image Storage | RAM (volatile): 16 GB, up to 26000 frames, full frame SSD (non-volatile): >4 TB |
| Radiometric Data Streaming | Simultaneous Gigabit Ethernet (GigE Vision), Camera Link, CoaXPress (CXP) |
| Standard Video | HDMI, SDI, NTSC, PAL |
| Command and Control | GigE, USB, RS-232, Camera Link, CXP (GenICam protocol supported over GigE or CXP) |



FLIR X6900sc SLS

P/N: 29421-200

© 2017, FLIR Systems, Inc.

#29421-200; r. /44554; en-US

| Temperature Measurement | |
|---|--|
| Standard Temperature Range | No calibrations available |
| Optional Temperature Range | No calibrations available |
| Accuracy | No calibrations available |
| Optics | |
| Camera f/Number | f/2.5 |
| Available Lenses (Uses FLIR HDC Optics) | No lenses available |
| Close-up Lenses/Microscopes | No microscopes available |
| Lens Interface | FLIR HDC (4-tab bayonet) |
| Focus | Manual |
| Filtering | 4-position motorized filter wheel, standard 1-inch filters |
| Image/Video Presentation | |
| Palettes | Selectable 8-bit |
| Automatic Gain Control | Manual, Linear, Plateau equalization, ROI, DDE |
| Overlay | Customizable (IRIG-B, Date, Integration time, Internal temp, Frame rate, Sync mode, Cooler hours) |
| Video Modes | HD: 720p/50/59.9 Hz, 1080p/25/29.9 Hz, SD: NTSC, PAL |
| Digital Zoom | 1x, 4x, 4:3 |
| General | |
| Operating Temperature Range | -20°C to 50°C (-4°F to 122°F) |
| Shock/Vibration | 40 g, 11 msec ½ sine pulse/4.3 g RMS random vibration, all 3 axes |
| Power | 24 VDC (< 50 W steady state) |
| Weight w/Handle, w/o Lens | 6.35 kg (14 lbs) |
| Size (L x W x H) w/o Lens, Handle | 249 x 158 x 147 mm (9.8 x 6.2 x 5.8 in.) |
| Mounting | <ul style="list-style-type: none"> • 2 x ¼ in. -20 • 1 x 3/8 in. -16 • 4 x #10-24 • Side: 3x ¼ in. -20 (each side) |

Supplies & accessories:





